

LIFE CYCLE ANALYSIS (LCA) IN THE ABSOILS PROJECT

Tarja Niemelin, Ramboll Finland

ABSOILS Conference, Helsinki 11.-12.9.2014

ABSOILS - LIFE09 ENV/FI/000575



- Methodology based on the ISO 14040 standard
- Compilation and evaluation of the inputs, outputs and the potential environmental impacts of a product system throughout the product's life time or a chosen lifetime period
- An incomplete LCA (Streamlined LCA) is possible in case there is shortage of time, money, data or other necessary resources to carry out a complete one
- For ABSOILS Verification a <u>Streamlined LCA</u> was carried out.

ABSOILS - LIFE09 ENV/FI/000575



The studied environmental impacts in each pilot:

- Depletion of natural resources
- Global warming potential GWP (CO₂, CH₄, N₂O)
- Energy consumption (not an actual environmental impact but the cause of airborne emissions)


Functional unit (FU) = Quantified performance of a product system for use as a reference unit

- Arcada FU = 100 m^2
- Dog Park FU = 100 m^2
- Jätkäsaari FU = m³

ABSOILS - LIFE09 ENV/FI/000575




Arcada structural alternatives:



Geotextile

Mass stabilisation of abandoned clay Binders: Alt 1: cement Alt 2: cement + fly ash

Natural clay deposit




Embankment 0,7 m

Geotextile

Light weight expanded clay (alt 3)


Geotextile Natural clay deposit



ABSOILS - LIFE09 ENV/FI/000575




Arcada results per functional unit (100 m²)




ABSOILS - LIFE09 ENV/FI/000575



Dog Park structural alternatives:



Overloading embankment Geotextile Mass stabilisation of abandoned clay and natural clay Binders: Alt 1: cement Alt 2: cement + fly ash Natural clay deposit




Removal of soft soil (1 m) and fill with light expanded clay aggregate (1,7 m)

ABSOILS - LIFE09 ENV/FI/000575



Dog Park results per functional unit (100 m²)



ABSOILS - LIFE09 ENV/FI/000575




Jätkäsaari structural alternatives:

- Alt 1 Mass stabilisation of the dredged sediments with cement, utilization of mass stabilised sediments in the park
- Alt 2 Mass stabilisation of the dredged sediments with cement and fly ash, utilization of mass stabilised sediments in the park
- Alt 3 The contaminated sediments are transported to the landfill (mass stabilised lightly with cement, so the transportation can be done), non-cohesive soils for park filling

ABSOILS - LIFE09 ENV/FI/000575



Jätkäsaari results per functional unit (m³)



ABSOILS - LIFE09 ENV/FI/000575



In conclusion:

- According to the studied environmental impacts the pilot structures seem to be more environmentally feasible than the conventional structures
- When interpreting the results, the functional unit (FU) must be considered and the results can be reliably compared only between the structure alternatives
- Utilisation of surplus soils and by-products is according the EU Waste Hierarchy

ABSOILS - LIFE09 ENV/FI/000575